


NOTE:

- TEMPORARY BRACING MAY BE REQUIRED TO RESIST PRESSURES FROM THE WET CONCRETE PLACED BEHIND THE VERSA-LOK UNITS DURING CONSTRUCTION
- CONCRETE FOUNDATIONS AND STEEL REINFORCEMENT SHOULD BE DESIGNED BY A QUALIFIED ENGINEER
- MINIMUM FROST DEPTH (Y) VARIES WITH REGION

20" REINFORCED COLUMN SECTION  
REINFORCED COLUMN  
SCALE: 1/2"=1'

THESE PRELIMINARY DETAILS ARE INTENDED AS AN AID IN DESIGNING ATTRACTIVE, DURABLE RETAINING WALLS WITH VERSA-LOK UNITS. FINAL DETERMINATION OF THE SUITABILITY OF ANY INFORMATION OR MATERIAL FOR THE USE CONTEMPLATED, AND ITS MANNER OF USE, IS THE SOLE RESPONSIBILITY OF THE USER. A FINAL PROJECT SPECIFIC DESIGN SHOULD BE PREPARED BY A QUALIFIED, LICENSED, PROFESSIONAL ENGINEER.



**VERSA-LOK**<sup>®</sup>  
Retaining Wall Systems

(800)770-4525 fax(651)770-4089  
6348 Hwy36 Ste1, Oakdale,MN 55128 **Solid Solutions**<sup>™</sup>

VERSA-LOK HARMONY DETAILS

20" REINFORCED COLUMN  
SECTION

SCALE:	AS NOTED
DRAWN BY:	PDL
CHECKED BY:	
DATE:	11/2015
DWG. NO.	HAR REINFORCED COLUMN SECTION