

COLUMN NOTES:


- MAY USE PRECAST CONCRETE PAD IN PLACE OF GRANULAR LEVELING PAD
- FOR COLUMNS TALLER THAN 4' PLACE CONCRETE AND REBAR WITHIN THE COLUMN, AND CONSTRUCT ON A REINFORCED CONCRETE FROST FOOTING. SEE REINFORCED COLUMN INSTALLATION SEQUENCE DETAIL

20" STANDARD COLUMN SECTION

STANDARD-UNREINFORCED COLUMN (4' TALL MAX.)

SCALE: NONE

THESE PRELIMINARY DETAILS ARE INTENDED AS AN AID IN DESIGNING ATTRACTIVE, DURABLE RETAINING WALLS WITH VERSA-LOK UNITS. FINAL DETERMINATION OF THE SUITABILITY OF ANY INFORMATION OR MATERIAL FOR THE USE CONTEMPLATED, AND ITS MANNER OF USE, IS THE SOLE RESPONSIBILITY OF THE USER. A FINAL PROJECT SPECIFIC DESIGN SHOULD BE PREPARED BY A QUALIFIED, LICENSED, PROFESSIONAL ENGINEER.



**VERSA-LOK®**  
Retaining Wall Systems

(800)770-4525 fax(651)770-4089  
6348 Hwy36 Ste1, Oakdale, MN 55128 **Solid Solutions™**

VERSA-LOK STANDARD DETAILS

20" UNREINFORCED COLUMN SECTION

SCALE: 3/4"=1'

DRAWN BY: PPS

CHECKED BY:

DATE: 10/2007

DWG. NO. strd unreinforced column section