



NOTES:

- TIGHTEST OUTSIDE (CONVEX) RADIUS VARIES DEPENDING ON STANDARD/COBBLE UNIT RATIO
- A 1:1 RATIO OF STANDARD/COBBLE UNITS YIELDS A MINIMUM RADIUS OF APPROXIMATELY 6'
- FOLLOW GEOGRID MANUFACTURER'S INSTRUCTIONS FOR REINFORCEMENT PLACEMENT AT CURVES AND CORNERS

THESE PRELIMINARY DETAILS ARE INTENDED AS AN AID IN DESIGNING ATTRACTIVE, DURABLE RETAINING WALLS WITH VERSA-LOK UNITS. FINAL DETERMINATION OF THE SUITABILITY OF ANY INFORMATION OR MATERIAL FOR THE USE CONTEMPLATED, AND ITS MANNER OF USE, IS THE SOLE RESPONSIBILITY OF THE USER. A FINAL PROJECT SPECIFIC DESIGN SHOULD BE PREPARED BY A QUALIFIED, LICENSED, PROFESSIONAL ENGINEER.



**VERSA-LOK®**  
Retaining Wall Systems

(800)770-4525 fax(651)770-4089  
6348 Hwy36 Ste1, Oakdale, MN 55128 **Solid Solutions™**

VERSA-LOK HARMONY DETAILS

CURVES

SCALE:	AS NOTED
DRAWN BY:	PDL
CHECKED BY:	
DATE:	12/2015
DWG. NO.	HAR CURVES